



AIC501 Datasheet

Single-Core Application Processor

Version 1.0

August 19, 2020

Revision History

Version	Date	Description
V1.0	2020-08-19	Initial release version

Declaration

THIS DOCUMENTATION IS THE ORIGINAL WORK AND COPYRIGHTED PROPERTY OF ARTINCHIP TECHNOLOGY(“ARTINCHIPTECH”).REPRODUCTION IN WHOLE OR IN PART MUST OBTAIN THE WRITTEN APPROVAL OF ARTMEM AND GIVE CLEAR ACKNOWLEDGEMENT TO THE COPYRIGHT OWNER.

THE PURCHASED PRODUCTS,SERVICES AND FEATURES ARE STIPULATED BY THE CONTRACT MADE BETWEEN ARTMEM AND THE CUSTOMER.PLEASE READ THE TERMS AND CONDITIONS OF THE CONTRACT AND RELEVANT INSTRUCTIONS CAREFULLY BEFORE USING,AND FOLLOW THE INSTRUCTIONS IN THIS DOCUMENTATION STRICTLY.ARTMEM ASSUMES NO RESPONSIBILITY FOR THE CONSEQUENCES OF IMPROPERUSE(INCLUDING BUT NOT LIMITED TO OVERVOLTAGE,OVERCLOCK,OR EXCESSIVE TEMPERATURE).

THE INFORMATION FURNISHED BY ARTMEM IS PROVIDED JUST AS A REFERENCE OR TYPICAL APPLICATIONS,ALL STATEMENTS,INFORMATION,AND RECOMMENDATIONS IN THIS DOCUMENT DO NOT CONSTITUTE A WARRANTY OF ANY KIND,EXPRESS OR IMPLIED.ARTMEM RESERVES THE RIGHT TO MAKE CHANGES IN CIRCUIT DESIGN AND/OR SPECIFICATIONS AT ANY TIME WITHOUT NOTICE.

NOR FOR ANY INFRINGEMENTS OF PATENTS OR OTHER RIGHTS OF THE THIRD PARTIES WHICH MAY RESULT FROM ITS USE.NO LICENSE IS GRANTED BY IMPLICATION OR OTHERWISE UNDER ANY PATENT OR PATENT RIGHTS OF ARTMEM.THIRD PARTY LICENCES MAY BE REQUIRED TO IMPLEMENT THE SOLUTION/PRODUCT.CUSTOMERS SHALL BE SOLELY RESPONSIBLE TO OBTAIN ALL APPROPRIATELY REQUIRED THIRD PARTY LICENCES.ARTMEM SHALL NOT BE LIABLE FOR ANY LICENCE FEE OR ROYALTY DUE IN RESPECT OF ANY REQUIREDTHIRD PARTY LICENCE.ARTMEM SHALL HAVE NO WARRANTY,INDEMNITY OR OTHER OBLIGATIONS WITH RESPECT TO MATTERS COVERED UNDER ANY REQUIRED THIRD PARTY LICENCE.

Table of Contents

1.	Overview.....	- 3 -
2.	Feature	- 4 -
2.1.	CPU Architecture	- 4 -
2.2.	Memory Subsystem.....	- 4 -
2.3.	System Peripherals	- 4 -
2.4.	Display Subsystem	- 5 -
2.5.	Video Engine.....	- 6 -
2.6.	Image Subsystem.....	- 6 -
2.7.	Audio Subsystem	- 7 -
2.8.	External Peripherals.....	- 7 -
2.9.	Package.....	- 8 -
3.	Block Diagram.....	- 9 -
4.	Pin Description	- 10 -
4.1.	Pin Characteristics	- 10 -
4.2.	GPIO Multiplexing Functions	- 14 -
4.3.	Detailed Pin/Signal Description	- 15 -
5.	Electrical Characteristics.....	- 19 -
5.1.	Absolute Maximum Ratings.....	- 19 -
5.2.	Recommended Operating Conditions	- 19 -
5.3.	DC Electrical Characteristics	- 20 -
5.4.	Oscillator Electrical Characteristics	- 20 -
6.	Pin Assignment	- 21 -
6.1.	Pin Map.....	- 21 -
6.2.	Package Dimension.....	- 22 -

1. Overview

The AIC501 integrates a single ARM Cortex™-A7 CPU that operates at speed up to 1GHz with supporting peripherals. A 128MB DDR3 is highly integrated in the AIC501. The processor has optimized external memory interfaces to SPI NAND/Nor flash, SD/MMC.

Dedicated video engine and audio subsystem are included to provide an advanced multimedia applications and services. Video Engine supports multi-format such as H.264 encoder by 1080p@60fps, H.264 decoder by 1080p@60fps, JPEG/MJPEG decoder by 1080p@30fps. Audio subsystem includes audio codec with dedicated hardware. To enrich camera feature, AIC501 equips an 8M HawkView™ ISP with advanced features like spatial de-noise, chrominance de-noise, zone-based AE/AF/AWB statistics, black level correction, lens shading correction, color correction and anti-flick detection statistics.

To reduce total system cost and enhance overall functionality, AIC501 has a broad range of hardware peripherals such as DMA, Timers, GPIO, UART, SPI, USB HS/FS OTG, TWI, EMAC etc.

2. Feature

2.1. CPU Architecture

- Single-Core ARM Cortex™ –A7 processor
- Thumb-2 Technology
- Support NEON Advanced SIMD(single instruction multiple data)instruction for acceleration of media and signal processing functions
- Support Large Physical Address Extensions(LPAE)
- VFPv4 Floating Point Unit
- 32KB L1 Instruction cache and 32KB L1 Data cache
- 128KB L2 cache

2.2. Memory Subsystem

Boot ROM

- On -chip memory
- Size:32KB
- Support system boot from the following device:
 - SPI Nor flash
 - SPI Nand flash
 - SD/TF card
 - eMMC flash
- Support system code download through USB OTG

SDRAM

- SIP 128MB DDR3

SD/MMC Interface

- Up to three SD/MMC controllers
- 1/4/8-bit SD,SDIO,MMC mode
- Complies with eMMC standard specification V4.41, SD physical layer specification V2.0, SDIO card specification V2.0
- Support hardware CRC generation and error detection
- Support block size from 1 to 65535 bytes

2.3. System Peripherals

Timer

- Three on-chip timers with interrupt-based operation
- One watchdogs to generate reset signal or interrupts
- 33 bits Audio/Video Sync(AVS) Counter
- 24MHz or Internal OSC clock input

High Speed Timer

- Up to two high speed timers

- Counters up to 56 bits
- Clock source is synchronized with AHB1 clock, much more accurate than other timers

RTC

- Time, calendar
- Counters second, minutes, hours, day, week, month and year with leap year generator
- Alarm: general alarm and weekly alarm
- One 32KHz fanout

GIC

- Support 16 SGIs(Software Generated Interrupt), 16 PPIs(Private Peripheral Interrupt) and 125 SPIs(Shared

Peripheral Interrupts)

DMA

- Up to 8-channel DMA
- Flexible data width of 8/16/32 bits
- Support linear and IO address modes
- Support data transfer types with memory-to-memory, memory-to-peripheral, peripheral-to-memory

CCU

- 9 PLLs
- One on-chip RC oscillator
- One 24MHz oscillator
- One 32.768KHz external oscillator
- Clock management: clock gating ,clock enabling to the device modules, clock reset, clock generation, clock

division

PWM

- Up to two PWM channels
- Support outputting two kinds of waveform: continuous waveform and pulse waveform
- 0% to 100% adjustable duty cycle
- Up to 24MHz output frequency

LRADC

- 6-bit resolution
- 1x channel
- Support hold key and continuous key
- Support single key, normal key and continuous key

Security Engine

- Crypto engine
 - Support AES 128/192/256-bits with ECB,CBC,CTS,CTR mode
 - Support DES/TDES with ECB,CBC,CTR mode
 - Support SHA1 and MD5
 - 160-bits hardware PRNG with 175-bits seed
- 256-bits EFUSE

2.4. Display Subsystem

DE2.0

- Output size up to 1024x1024
- Support three alpha blending channel for main display
- Support four overlay layers in each channel, and has a independent scale
- Support potter-duff compatible blending operation
- Support input format YUV422/ YUV420/ YUV411/ ARGB8888/ XRGB8888/ RGB888/ ARGB4444/ ARGB1555/ RGB 565

Display Output

- Support LVDS interface with single link, up to 1024x768@60fps
- Support RGB interface with DE/SYNC mode, up to 1024x768@60fps
- Support serial RGB/dummy RGB/CCIR656 interface, up to 800x480@60fps
- Support i80 interface with 18/16/9/8 bit, support TE, up to 800x480@60fps
- Support pixel format: RGB888, RGB666 and RGB565
- Dither function from RGB666/RGB565 to RGB888
- Gamma correction with R/G/B channel independence

2.5. Video Engine

Video Decoding

- Support video decoder for H.264 and JPEG/MJPEG
- Support H.264 BP/MP/HP up to 1080p@60fps
- Support H.264 output formats :NV21,NV12,YU12,YV12
- Support JPEG/MJPEG up to 1080p@30fps

Video Encoding

- Support H.264 video encoding up to 1080p@60fps, 720p@120fps
- JPEG baseline: picture size up to 8192x8192
- Support input picture size up to 4800x4800
- Support input formats: YU12/YV12/NV12/NV21/YUYV/YVYU/UYVY/VYUY
- Support Alpha blending
- Support thumb generation
- Support 4x2 scaling ratio: from 1/16 to 64 arbitrary non-integer ratio
- Support rotated input

2.6. Image Subsystem

Image Input

- Support 8/10/12-bits CMOS sensor parallel interface
- Support 8bit CCIR656 protocol for NTSC and PAL
- Support ITU-R BT 1120 protocol for HD-CIF system
- Support 16bit interface with separate syncs
- Support Format:
 - YUV422-8/10 bit
 - RAW-8/10/12bit

- Performance:
 - Still capture resolution up to 5M with parallel interface
 - Video capture resolution up to 1080p@30fps with parallel interface

ISP

- Support input formats:8/10-bits RAW RGB,8-bits YCbCr
- Support output formats: YCbCr420 semi-planar,YCrCb420 semi-planar, YCbCr422 semi-planar,YCrCb422 semi-planar,YUV420 planar,YUV422 planar
 - Support image mirror flip and rotation
 - Support two output channels
 - Speed up to 8MPixels@24fps
 - Defect pixel correction
 - Super lens shading correction
 - Anisotropic non-linear Bayer interpolation with false color suppression
 - Programmable color correction
 - Advanced contrast enhance and sharpening
 - Advanced saturation adjust
 - Advanced spatial(2D) de-noise filter
 - Advanced chrominance noise reduction
 - Zone-based AE/AF/AWB statistics
 - Anti-flick detection statistics
 - Histogram statistics

2.7. Audio Subsystem

Audio Codec

- Two audio digital-to-analog(DAC) channels
- Support analog/digital volume control
- Support Dynamic Range Controller adjusting the DAC playback output(DRC)
- Stereo Headphone output

2.8. External Peripherals

USB

- One USB 2.0 OTG controller with PHY
- Complies with USB2.0 Specification
- Support High-Speed(HS,480Mbps),Full-Speed(FS,12Mbps),and Low-Speed(LS,1.5Mbps) in host mode
- Complies with Enhanced Host Controller Interface (EHCI) Specification, Version 1.0,and the Open Host Controller Interface(OHCI) Specification,Version 1.0a for host mode
 - Up to 8 User-Configurable Endpoints in device mode
 - Support point-to-point and point-to-multipoint transfer in both host and peripheral mode

Ethernet

- Integrated an internal 10/100M PHY
- Support 10/100Mbps data transfer rate

- Support full-duplex and half-duplex operation
- Support linked-list descriptor list structure
- Programmable frame length to support Standard or Jumbo Ethernet frames with sizes up to 16 KB
- Support a variety of flexible address filtering modes

UART

- Up to three UART controllers
- 64-Bytes Transmit and receive data FIFOs for all UART
- Compliant with industry-standard 16550 UARTs
- Support Infrared Data Association (IrDA) 1.0 SIR

SPI

- Full-duplex synchronous serial interface
- Master/Slave configurable
- Mode0~3 supported for both transmit and receive operations
- Support single and dual read mode
- Two 64-Bytes FIFO for SPI-TX and SPI-RX operation
- DMA-based or interrupt-based operation
- SPI Clock (SPI_CLK) configurable

TWI

- Up to Two Wire Interface (TWI) controllers
- Support Standard mode (up to 100K bps) and Fast mode (up to 400K bps)
- Master/Slave configurable
- Allows 10-bit addressing transactions

2.9. Package

- eLQFP128, 16mm*16mm, 0.4mm Pitch

3. Block Diagram

The following figure shows the block diagram of AIC501 processor.




Figure 3-1. AIC501 Block Diagram

4. Pin Description

4.1. Pin Characteristics

Table 4-1 lists the characteristics of AIC501 Pins from seven aspects.

[1].Pin#: Package pin numbers associated with each signals.

[2].Pin Name: The name of the package pin.

[3].Type: Denotes the signal direction

- I (Input),
- O (Output),
- I/O (Input/Output),
- OD (Open-Drain),
- A (Analog),
- AI (Analog Input),
- AO (Analog Output),
- P (Power),
- G (Ground)

[4].Pin Reset State: The state of the terminal at reset. PU: pull up; PD: pull down; Z: high impedance.

[5].Pull Up/Down: Denotes the presence of an internal pull-up or pull-down resistor. Pull-up and pull-down resistors can be enabled or disabled by software.

[6].Default Buffer Strength: Defines default drive strength of the associated output buffer. The maximum drive strength of each GPIO is 6mA.

[7].Power Supply: The voltage supply for the terminal's IO buffers.

Table 4-1. Pin Characteristics

Pin#[1]	Pin Name[2]	Type[3]	Pin Reset State[4]	Pull Up/Down[5]	Default Buffer Strength (mA)[6]	Power Supply[7]
DRAM						
75	ZQ	AI	Z	NA	NA	VCC-DRAM
71	SVREF	AI	Z	NA	NA	VCC-DRAM
67	DVREF	AI	Z	NA	NA	VCC-DRAM
68,69,70,72,73,74	VCC-DRAM	P	NA	NA	NA	NA
GPIO B						
42	PB0	I/O	Z	PU/PD	20	VCC-IO
43	PB1	I/O	Z	PU/PD	20	VCC-IO
44	PB4	I/O	Z	PU/PD	20	VCC-IO
45	PB5	I/O	Z	PU/PD	20	VCC-IO
46	PB6	I/O	Z	PU/PD	20	VCC-IO
47	PB7	I/O	Z	PU/PD	20	VCC-IO
48	PB8	I/O	Z	PU/PD	20	VCC-IO
49	PB9	I/O	Z	PU/PD	20	VCC-IO

Pin# ^[1]	Pin Name ^[2]	Type ^[3]	Pin Reset State ^[4]	Pull Up/Down ^[5]	Default Buffer Strength (mA) ^[6]	Power Supply ^[7]
GPIO C						
52	PC0	I/O	Z	PU/PD	20	VCC-IO
53	PC1	I/O	Z	PU/PD	20	VCC-IO
54	PC2	I/O	Z	PU/PD	20	VCC-IO
55	PC3	I/O	Z	PU/PD	20	VCC-IO
56	PC4	I/O	Z	PU/PD	20	VCC-IO
57	PC5	I/O	Z	PU/PD	20	VCC-IO
59	PC6	I/O	Z	PU/PD	20	VCC-IO
60	PC7	I/O	Z	PU/PD	20	VCC-IO
61	PC8	I/O	Z	PU/PD	20	VCC-IO
62	PC9	I/O	Z	PU/PD	20	VCC-IO
63	PC10	I/O	Z	PU/PD	20	VCC-IO
GPIO D						
16	PD12	I/O	Z	PU/PD	20	VCC-IO
15	PD13	I/O	Z	PU/PD	20	VCC-IO
18	PD14	I/O	Z	PU/PD	20	VCC-IO
17	PD15	I/O	Z	PU/PD	20	VCC-IO
21	PD16	I/O	Z	PU/PD	20	VCC-IO
20	PD17	I/O	Z	PU/PD	20	VCC-IO
23	PD18	I/O	Z	PU/PD	20	VCC-IO
22	PD19	I/O	Z	PU/PD	20	VCC-IO
25	PD20	I/O	Z	PU/PD	20	VCC-IO
24	PD21	I/O	Z	PU/PD	20	VCC-IO
GPIO E						
41	PE0	I/O	Z	PU/PD	20	VCC-IO
40	PE1	I/O	Z	PU/PD	20	VCC-IO
39	PE2	I/O	Z	PU/PD	20	VCC-IO
38	PE3	I/O	Z	PU/PD	20	VCC-IO
37	PE4	I/O	Z	PU/PD	20	VCC-IO
36	PE5	I/O	Z	PU/PD	20	VCC-IO
35	PE6	I/O	Z	PU/PD	20	VCC-IO
34	PE7	I/O	Z	PU/PD	20	VCC-IO
33	PE8	I/O	Z	PU/PD	20	VCC-IO
32	PE9	I/O	Z	PU/PD	20	VCC-IO
29	PE10	I/O	Z	PU/PD	20	VCC-IO
28	PE11	I/O	Z	PU/PD	20	VCC-IO
27	PE12	I/O	Z	PU/PD	20	VCC-IO
13	PE13	I/O	Z	PU/PD	20	VCC-IO
12	PE14	I/O	Z	PU/PD	20	VCC-IO
11	PE15	I/O	Z	PU/PD	20	VCC-IO
10	PE16	I/O	Z	PU/PD	20	VCC-IO
9	PE17	I/O	Z	PU/PD	20	VCC-IO

Pin# ^[1]	Pin Name ^[2]	Type ^[3]	Pin Reset State ^[4]	Pull Up/Down ^[5]	Default Buffer Strength (mA) ^[6]	Power Supply ^[7]
8	PE18	I/O	Z	PU/PD	20	VCC-IO
6	PE19	I/O	Z	PU/PD	20	VCC-IO
5	PE20	I/O	Z	PU/PD	20	VCC-IO
4	PE21	I/O	Z	PU/PD	20	VCC-IO
3	PE22	I/O	Z	PU/PD	20	VCC-IO
2	PE23	I/O	Z	PU/PD	20	VCC-IO
1	PE24	I/O	Z	PU/PD	20	VCC-IO
GPIO F						
102	PF0	I/O	Z	PU/PD	20	VCC-IO
101	PF1	I/O	Z	PU/PD	20	VCC-IO
100	PF2	I/O	Z	PU/PD	20	VCC-IO
98	PF3	I/O	Z	PU/PD	20	VCC-IO
97	PF4	I/O	Z	PU/PD	20	VCC-IO
96	PF5	I/O	Z	PU/PD	20	VCC-IO
95	PF6	I/O	Z	PU/PD	20	VCC-IO
GPIO G						
128	PG0	I/O	Z	PU/PD	20	VCC-IO
127	PG1	I/O	Z	PU/PD	20	VCC-IO
126	PG2	I/O	Z	PU/PD	20	VCC-IO
125	PG3	I/O	Z	PU/PD	20	VCC-IO
124	PG4	I/O	Z	PU/PD	20	VCC-IO
123	PG5	I/O	Z	PU/PD	20	VCC-IO
122	PG6	I/O	Z	PU/PD	20	VCC-IO
121	PG7	I/O	Z	PU/PD	20	VCC-IO
120	PG8	I/O	Z	PU/PD	20	VCC-IO
119	PG9	I/O	Z	PU/PD	20	VCC-IO
RTC&PLL						
92	RTC-VIO	P	-	-	-	-
91	X32KIN	A	-	-	-	-
90	X32KOUT	A	-	-	-	-
93	VCC-RTC	P	-	-	-	-
78	VCC-PLL	P	-	-	-	-
System Control						
94	RESET	I	-	-	-	-
77	X24MIN	A	-	-	-	-
76	X24MOUT	A	-	-	-	-
USB						
106	VCC-USB	P	-	-	-	-
104	USB-DM	A	-	-	-	-
105	USB-DP	A	-	-	-	-
Audio Codec						
108	AVCC	P	-	-	-	-

Pin# ^[1]	Pin Name ^[2]	Type ^[3]	Pin Reset State ^[4]	Pull Up/Down ^[5]	Default Buffer Strength (mA) ^[6]	Power Supply ^[7]
109	AGND	G	-	-	-	-
110	VRA1	A	-	-	-	-
111	VRA2	A	-	-	-	-
112	HPOUTR	A	-	-	-	-
113	HPOUTL	A	-	-	-	-
114	HPVCCIN	P	-	-	-	-
115	HPVCCBP	A	-	-	-	-
116	HPCOM	A	-	-	-	-
EPHY						
79	EPHY-LINK-LED	O	-	-	-	-
80	EPHY-SPD-LED	O	-	-	-	-
83	VDD-EPHY	P	-	-	-	-
84	EPHY-RXN	A	-	-	-	-
85	EPHY-RXP	A	-	-	-	-
86	EPHY-TXN	A	-	-	-	-
87	EPHY-TXP	A	-	-	-	-
88	VCC- EPHY	P	-	-	-	-
89	EPHY-RTX	A	-	-	-	-
LRADC						
107	LRADC0	A	-	-	-	-
Power						
7, 19, 31, 50, 64, 99, 118	VCC-IO	P	-	-	-	-
14, 65, 66, 82, 103, 117	VDD-SYS	P	-	-	-	-
26, 30, 51, 58	VDD-CPU	P	-	-	-	-
EPAD	GND	P	-	-	-	-
TEST						
TEST	TEST	A	-	-	-	-

4.2. GPIO Multiplexing Functions

The following table provides a description of the AIC501 GPIO multiplexing functions.

Table 4-2. Multiplexing Functions

Pin Name	GPIO Group	IO Type	Function 2	Function3	Function 4	Function 5	Function 6
PB0	GPIOB	I/O	UART2_TX				PB_EINT0
PB1		I/O	UART2_RX				PB_EINT1
PB4		I/O	PWM0				PB_EINT4
PB5		I/O	PWM1				PB_EINT5
PB6		I/O	TWI0_SCK				PB_EINT6
PB7		I/O	TWI0_SDA				PB_EINT7
PB8		I/O	TWI1_SCK	UART0_TX			PB_EINT8
PB9		I/O	TWI1_SDA	UART0_RX			PB_EINT9
PC0		GPIOC	I/O	SDC2_CLK	SPIO_MISO		
PC1	I/O		SDC2_CMD	SPIO_CLK			
PC2	I/O		SDC2_RST	SPIO_CS			
PC3	I/O		SDC2_D0	SPIO_MOSI			
PC4	I/O		SDC2_D1				
PC5	I/O		SDC2_D2				
PC6	I/O		SDC2_D3				
PC7	I/O		SDC2_D4				
PC8	I/O		SDC2_D5				
PC9	I/O		SDC2_D6				
PC10	I/O		SDC2_D7				
PD12	GPIOD	I/O		LVDS_VP0			
PD13		I/O		LVDS_VN0			
PD14		I/O		LVDS_VP1			
PD15		I/O		LVDS_VN1			
PD16		I/O		LVDS_VP2			
PD17		I/O		LVDS_VN2			
PD18		I/O		LVDS_VPC			
PD19		I/O		LVDS_VNC			
PD20		I/O		LVDS_VP3			
PD21		I/O		LVDS_VN3			
PE0	GPIOE	I/O	CSI_PCLK	LCD_CLK			
PE1		I/O	CSI_MCLK	LCD_DE			
PE2		I/O	CSI_HSYNC	LCD_HSYNC			
PE3		I/O	CSI_VSYNC	LCD_VSYNC			
PE4		I/O	CSI_D0	LCD_D2			
PE5		I/O	CSI_D1	LCD_D3			
PE6		I/O	CSI_D2	LCD_D4			
PE7		I/O	CSI_D3	LCD_D5			
PE8		I/O	CSI_D4	LCD_D6			

Pin Name	GPIO Group	IO Type	Function 2	Function3	Function 4	Function 5	Function 6	
PE9		I/O	CSI_D5	LCD_D7				
PE10		I/O	CSI_D6	LCD_D10				
PE11		I/O	CSI_D7	LCD_D11				
PE12		I/O	CSI_D8	LCD_D12				
PE13		I/O	CSI_D9	LCD_D13				
PE14		I/O	CSI_D10	LCD_D14				
PE15		I/O	CSI_D11	LCD_D15				
PE16		I/O	CSI_D12	LCD_D18				
PE17		I/O	CSI_D13	LCD_D19				
PE18		I/O	CSI_D14	LCD_D20				
PE19		I/O	CSI_D15	LCD_D21				
PE20		I/O	CSI_FIELD					
PE21		I/O	CSI_SCK	TWI1_SCK	UART1_TX			
PE22		I/O	CSI_SDA	TWI1_SDA	UART1_RX			
PE23					LCD_D22	UART1_RTS		
PE24					LCD_D23	UART1_CTS		
PF0	GPIOF	I/O	SDC0_D1					
PF1		I/O	SDC0_D0					
PF2		I/O	SDC0_CLK	UART0_TX				
PF3		I/O	SDC0_CMD					
PF4		I/O	SDC0_D3	UART0_RX				
PF5		I/O	SDC0_D2					
PF6		I/O						
PG0	GPIOG	I/O	SDC1_CLK				PG_EINT0	
PG1		I/O	SDC1_CMD				PG_EINT1	
PG2		I/O	SDC1_D0				PG_EINT2	
PG3		I/O	SDC1_D1				PG_EINT3	
PG4		I/O	SDC1_D2				PG_EINT4	
PG5		I/O	SDC1_D3				PG_EINT5	
PG6		I/O	UART1_TX				PG_EINT6	
PG7		I/O	UART1_RX				PG_EINT7	
PG8		I/O	UART1_RTS				PG_EINT8	
PG9		I/O	UART1_CTS				PG_EINT9	

4.3. Detailed Pin/Signal Description

Table 4-3 shows the detailed function of every pin/signal based on the different interface.

Table 4-3.Detailed Pin Description

Pin/Signal Name	Description	Type
DRAM		
ZQ	DDR calibrated resistor	AI

Pin/Signal Name	Description	Type
SVREF	DRAM Reference Voltage Input	AI
DVREF	DRAM Reference Voltage Input	AI
VCC-DRAM	DRAM Power Supply	P
System Control		
RESET	RESET Signal	I
X24MIN	Clock Input Of 24MHz Crystal	AI
X24MOUT	Clock Output Of 24MHz Crystal	AO
RTC		
RTC-VIO	Internal LDO Output Bypass	P
X32KIN	Clock input of 32768Hz Crystal	AI
X32KOUT	Clock output of 32768Hz Crystal	AO
VCC-RTC	RTC Power Supply	P
VCC-PLL	PLL Power Supply	P
USB		
VCC-USB	USB Power Supply	P
USB-DM	USB data signal DM	AI/O
USB-DP	USB data signal DP	AI/O
LRADC		
LRADC0	ADC input for key0	AI
Audio Codec		
AVCC	Power Supply for Analog Part	P
AGND	Ground for Analog Part	G
VRA1	Reference Voltage	AO
VRA2	Reference Voltage	AO
HPOUTR	Headphone Output Right Channel	AO
HPOUTL	Headphone Left Right Channel	AO
HPVCCIN	Headphone VCC Input	P
HPVCCBP	Headphone VCC Bypass	AO
HPCOM	Headphone Common Reference Output	AO
EPHY		
EPHY-LINK-LED	EPHY LINK Up/Down Indicator LED	AI/O
EPHY-SPD-LED	EPHY 10M/100M Indicator LED	AI/O
VDD-EPHY	Analog Power Supply for EPHY	P
EPHY-RXN	Transceiver Negative Output/Input	AI/O
EPHY-RXP	Transceiver Positive Output/Input	AI/O
EPHY-TXN	Transceiver Negative Output/Input	AI/O
EPHY-TXP	Transceiver Positive Output/Input	AI/O
VCC- EPHY	Analog Power Supply for EPHY	P
EPHY-RTX	EPHY External Resistance to Ground	AI
SD/MMC		
SDC0_CMD	Command Signal for SD/TF Card	I/O
SDC0_CLK	Clock for SD/TF Card	O
SDC0_D[3:0]	Data Input and Output for SD/TF Card	I/O

Pin/Signal Name	Description	Type
SDC1_CMD	Command Signal for SD/TF Card / SDIO	I/O
SDC1_CLK	Clock for SD/TF Card / SDIO	O
SDC1_D[3:0]	Data Input and Output for SD/TF Card / SDIO	I/O
SDC2_CMD	Command Signal for SD/TF Card / EMMC	I/O
SDC2_CLK	Clock for SD/TF Card / EMMC	O
SDC2_D[7:0]	Data Input and Output for SD/TF Card / EMMC	I/O
Interrupt		
PB_EINT[1:0]\[9:4]	GPIO B Interrupt	I
PG_EINT[24:0]	GPIO G Interrupt	I
PWM		
PWM0	Pulse Width Modulation output channel0	O
PWM1	Pulse Width Modulation output channel1	O
LCD		
LCD_D[23:0]	LCD Data Output	O
LCD_CLK	LCD Clock Signal	O
LCD_DE	LCD Data Enable	O
LCD_HSYNC	LCD Horizontal SYNC	O
LCD_VSYNC	LCD Vertical SYNC	O
LVDS		
LVDS_VP[3:0]	LVDS Data Positive Signal Output	AO
LVDS_VN[3:0]	LVDS Data Negative Signal Output	AO
LVDS_VPC	LVDS Clock Positive Signal Output	AO
LVDS_VNC	LVDS Clock Negative Signal Output	AO
CSI		
CSI_PCLK	CSI Pixel Clock	I
CSI_MCLK	CSI Master Clock	O
CSI_HSYNC	CSI Horizontal SYNC	I
CSI_VSYNC	CSI Vertical SYNC	I
CSI_D[15:0]	CSI Data Input	I
CSI_SCK	CSI Command Serial Clock Signal	I/O
CSI_SDA	CSI Command Serial Data Signal	I/O
CSI_FIELD	CSI Field Signal	I/O
SPI		
SPI0_CS	SPI Chip Select signal, low active	I/O
SPI0_CLK	SPI Clock signal	I/O
SPI0_MOSI	SPI Master data Out, Slave data In	I/O
SPI0_MISO	SPI Master data In, Slave data Out	I/O
UART		
UART0_TX	UART0 Data Transmit	O
UART0_RX	UART0 Data Receive	I
UART1_TX	UART1 Data Transmit	O
UART1_RX	UART1 Data Receive	I

Pin/Signal Name	Description	Type
UART1_CTS	UART1 Data Clear To Send	I
UART1_RTS	UART1 Data Request To Send	O
UART2_TX	UART2 Data Transmit	O
UART2_RX	UART2 Data Receive	I
UART2_CTS	UART2 Data Clear To Send	I
UART2_RTS	UART2 Data Request To Send	O
TWI		
TWI0_SCK	TWI0 Serial Clock Signal	I/O
TWI0_SDA	TWI0 Serial Data Signal	I/O
TWI1_SCK	TWI1 Serial Clock Signal	I/O
TWI1_SDA	TWI1 Serial Data Signal	I/O
Power		
VCC-IO	IO Power	P
VDD-SYS	System Power	P
VDD-CPU	CPU Power	P
GND	Ground for Power and Signals	P
TEST		
TEST	Connect to Ground	-

5. Electrical Characteristics

5.1. Absolute Maximum Ratings

Functional operation of the device at these or any other conditions beyond the absolute maximum ratings listed in Table 5-1 can cause permanent damage to the device.

Table 5-1. Absolute Maximum Ratings

Symbol	Parameter	Min	Max	Unit
T _{STG}	Storage Temperature	-40	125	°C
AVCC	Power Supply for Analog part	-0.3	3.6	V
EPHY-VCC	Power Supply for EPHY	-0.3	3.6	V
EPHY-VDD	Power Supply for EPHY	-0.3	1.4	V
HPVCCIN	Power Supply for Headphone	-0.3	3.6	V
VCC-IO	Power Supply for IO	-0.3	3.6	V
VCC-PLL	Power Supply for PLL	-0.3	3.6	V
VCC-RTC	Power Supply for RTC	-0.3	3.6	V
VCC-USB	Power Supply for USB	-0.3	3.6	V
VCC-DRAM	Power Supply for DDR3 DRAM	-0.3	1.65	V
VCC-CPU	Power Supply for CPU	-0.3	1.4	V
VCC-SYS	Power Supply for System	-0.3	1.4	V
I _{I/O}	In/Out current for input and output	-40	40	mA

5.2. Recommended Operating Conditions

All AIC501 modules are used under the operating Conditions contained in Table 5-2.

Table 5-2. Recommended Operating Conditions

Symbol	Parameter	Min	Typ	Max	Unit
T _a	Ambient Temperature	-20	-	85	°C
AVCC	Power Supply for Analog part	2.8	3.0	3.3	V
EPHY-VCC	Power Supply for EPHY	2.8	3.3	3.6	V
EPHY-VDD	Power Supply for EPHY	1.0	1.1	1.2	V
HPVCCIN	Power Supply for Headphone	3.0	3.3	3.6	V
VCC-IO	Power Supply for IO	1.7	1.8~3.3	3.6	V
VCC-PLL	Power Supply for PLL	2.7	3.0	3.3	V
VCC-RTC	Power Supply for RTC	3.0	3.3	3.6	V
VCC-USB	Power Supply for USB	3.0	3.3	3.45	V
VCC-DRAM	Power Supply for DRAM	1.425	1.5	1.575	V
VCC-CPU	Power Supply for CPU	-	1.2	-	V
VCC-SYS	Power Supply for System	-	1.2	-	V

5.3. DC Electrical Characteristics

Table 5-3 summarizes the DC electrical characteristics of AIC501.

Table 5-3. DC Electrical Characteristics

Symbol	Parameter	Min	Typ	Max	Unit
V _{IH}	High-Level Input Voltage	0.7*VCC-IO	-	VCC-IO + 0.3	V
V _{IL}	Low-Level Input Voltage	-0.3	-	0.3*VCC-IO	V
R _{PU}	Input Pull-up Resistance	50	100	150	KΩ
R _{PD}	Input Pull-down Resistance	50	100	150	KΩ
I _{IH}	High-Level Input Current	-	-	10	uA
I _{IL}	Low-Level Input Current	-	-	10	uA
V _{OH}	High-Level Output Voltage	VCC-IO -0.2	-	VCC-IO	V
V _{OL}	Low-Level Output Voltage	0	-	0.2	V
I _{oz}	Tri-State Output Leakage Current	-10	-	10	uA
C _{IN}	Input Capacitance	-	-	5	pF
C _{OUT}	Output Capacitance	-	-	5	pF

5.4. Oscillator Electrical Characteristics

The AIC501 contains two oscillators: a 24MHz oscillator and a 32768Hz oscillator. Each oscillator requires a specific crystal. The AIC501 device operation requires the following two input clocks:

The 32.768kHz frequency is used for low frequency operation.

The 24.000MHz frequency is used to generate the main source clock of the AIC501 device.



Table 5-4. 24MHz Oscillator Characteristics

Symbol	Parameter	Min	Typ	Max	Unit
1/(t _{CPMAIN})	Crystal Oscillator Frequency Range	-	24.000	-	MHz
	Frequency Tolerance at 25 °C	-40	-	+40	ppm
	Oscillation Mode	Fundamental			-

Table 5-5. 32.768kHz Oscillator Characteristics

Symbol	Parameter	Min	Typ	Max	Unit
1/(t _{CPMAIN})	Crystal Oscillator Frequency Range	-	32768	-	Hz
	Frequency Tolerance at 25 °C	-40	-	+40	ppm
	Oscillation Mode	Fundamental			-

6.2. Package Outline Dimension



Symbol	Dimension in mm			Dimension in inch		
	Min	Nom	Max	Min	Nom	Max
A	—	—	1.60	—	—	0.063
A ₁	0.05	—	—	0.002	—	—
A ₂	1.35	1.40	1.45	0.053	0.055	0.057
b	0.13	0.18	0.23	0.005	0.007	0.009
b ₁	0.13	0.16	0.19	0.005	0.006	0.007
c	0.09	—	0.20	0.004	—	0.008
c ₁	0.09	—	0.16	0.004	—	0.006
D	15.85	16.00	16.15	0.624	0.630	0.636
D ₁	13.90	14.00	14.10	0.547	0.551	0.555
E	15.85	16.00	16.15	0.624	0.630	0.636
E ₁	13.90	14.00	14.10	0.547	0.551	0.555
ⓐ	0.40 BSC			0.016 BSC		
L	0.45	0.60	0.75	0.018	0.024	0.030
L ₁	1.00 REF			0.039 REF		
R ₁	0.08	—	—	0.003	—	—
R ₂	0.08	—	0.20	0.003	—	0.008
S	0.20	—	—	0.008	—	—
θ	0°	3.5°	7°	0°	3.5°	7°
θ ₁	0°	—	—	0°	—	—
θ ₂	12° TYP			12° TYP		
θ ₃	12° TYP			12° TYP		
ccc	0.08			0.003		